



KÖSTER Color-Chips

Decorative colored chips for broadcasting into e.g. KÖSTER CT 215 Universal Floor, KÖSTER CT 227 1C Silane, and other resin products

Features

UV and chemically resistant decorative colored chips for broadcasting into the surface of KÖSTER CT 215 Universal Floor, KÖSTER CT 227 1C Silane, etc.

for a minimum of 2 years.

Technical Data

Size approx. 2 mm
Colors:
CT 429 001 white, light gray, gray
CT 429 002 black, gray
CT 429 003 black, gray, blue
CT 429 004 white, beige, brown

*Other colors available upon request.

Related products

KÖSTER CT 215 Universal Floor RAL7035 light grey	Prod. code CT 215 RAL7035
KÖSTER CT 227 1C Silane	Prod. code CT 227
KÖSTER TS transparent	Prod. code CT 320
KÖSTER Top Coat 1C Matte	Prod. code CT 325
KÖSTER CT 327 1C Sealer	Prod. code CT 327 005

Fields of Application

For adding surface structure and decoratively enhancing the surface of KÖSTER CT 215 Universal Floor, KÖSTER CT 227 1C Silane, etc. KÖSTER Color Chips are suitable for indoor and outdoor use.

Substrate

For all water based and solvent free resin coatings, especially KÖSTER CT 215 Universal Floor and KÖSTER CT 227 1C Silane.

Application

For use with KÖSTER CT 215 Universal Floor or KÖSTER CT 227 1C Silane:

For contrast floor decoration approx 50 g / m² of KÖSTER Color-Chips are evenly applied with a compressed air-powered cup gun. When broadcasting over the entire surface, approx. 0.7 - 1.0 kg / m² of KÖSTER Color-Chips are applied evenly in excess, also with a cup gun. After the coating has hardened, excess material can be picked up with an industrial vacuum cleaner and reused for further coating works. Protruding KÖSTER Color-Chips can be sanded with 120 grit sandpaper to level the surface. Alternatively, you can break the tips with a metal scraper.

When applying the sealing coat made of KÖSTER CT 327 1C Silane Sealer, we recommend wearing spiked shoes.

Consumption

Minimum 50 g / m² as a decorative, non-covering surface decoration. Approx. 0.7 - 1.0 kg / m² when broadcasting to rejection.

Packaging

CT 429 001	white, light grey, grey - 5 kg
CT 429 002	black, grey - 5 kg
CT 429 003	black, grey, blue - 5 kg
CT 429 004	white, beige, brown - 5 kg

Storage

Store in a cool and dry area. Carefully reseal opened cartons. If stored in originally sealed packages the KÖSTER Color Chips can be stored

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.